

TL2000-R

PRO series

Produkt Navn: TL2000-R

Produkt Nummer: 80040A

Description

Rechargeable SMD task lamp with 800 + 2000 lumens, anti-glare frosted front and Multigrip clip-on fixation

Specifications

Housing

Casing: ABS + PC, black. Rubber bumper: Silica gel, grey (matt).

Lens

Durable PC front.

Switch

Silica gel, red

Magnet

N/A

Hook

N/A

Foot stand

Durable ABS. 180° flexible with one 8 mm hole to fix to tripod

Battery type

6 x 18650. 11.1V - 4000mAh - 44.4Wh - Lithium rechargeable (50g)

Light source

66 x SMD 2835, 20W

Colour temperature (Kelvin)

6000K

Colour rendering index (CRI)

>80

Charger operating voltage

Required input: 100V-240V, 50-60Hz, 0.35A

Charger output

Required output: DC12.6V - 0.95A

Output (lumen)

800 (step 1), 2000 (step 2)

Run time (hours)

6 (at 800lm), 2.5-3 (at 2000lm)

Charging time (hours)

5-5.5

Charging level indicator

5 x LED on lamp

Protection class

IP65 (lamp), IP20 (charger) / IK08 / III (lamp), II (charger)

Operating temperature range (Celsius)

-10°C to +40°C

Charging port

For jack OD5.45mm + for charging pin ID2.0mm

Charging port cover

Silica gel, red

Power supply cable

1m, fixed on charger. With jack OD5.45mm + charging pin ID2.0mm

Power supply plug

Round EU 2 pin

240V power outlet

N/A

Additional data

5V 1A USB output built into lamp. Beam angle 100°



General Information

Lamp weight (g)

900

Lamp dimensions (cm)

23.9 x 20.3 x 7.2

EAN code box (1 pc)

5703296800402

EAN code inner carton

N/A

EAN code outer carton = 4 lamps

5703296810401

Harmonized standard code

8513100000

Packaging

Description

"PRO" design colour box

Box size (cm)

26.5 x 21.5 x 7.5

Box weight (g)

1180

Carton quantity (pcs)

4 (outer carton)

Carton size (cm)

32.5 x 27 x 23.5 (outer carton)

Carton weight (kg)

5.1 (outer carton)



Features

Durable task lamp with anti-glare frosted front

Rechargeable

Charging indicator (5 x LED), flash = charging / no flash = fully charged

Press button to check battery load status

Switch mode: on-800lm-2000lm-off

Reflector shaped to give approx. 110° beam angle

Supplied with EU 2 pin charger

5V 1A USB output built into lamp

Foot stand 180° flexible with hole to fix to tripod

Multi Grip - easy clip on fixation of other accessories

Low battery warning: front flashes 4-6 times approx. 10 minutes before battery runs out

Constant lumen output until battery runs out

Lamp can be used during charging (at 800lm output).

Tripod available as accessory



Elwis Lighting A/S Sandtoften 11, 2820 Gentofte, DK
www.elwislighting.com - Tel. +45 70 20 10 24

Version 1a 06/2019
© Elwis Lighting 2019
All details without
obligation